

TECNET ESPUMACID

FOAM DESCALER

Removes limestone and inorganic residues

Cleans and sanitizes in a single operation

Efficacy guaranteed with Air Foam System

APPLICATIONS

Foaming detergent to remove inorganic deposits, sanitize and cleanse machinery, plants and surfaces in food industry.

FEATURES

Formula generating a high-active and low water foam, granting a high gripping power on vertical surfaces; the best result is obtained with proper frothers, fixed or moveable.

It carries out in a single operation the descaling, sanitizing and cleansing effects.

INSTRUCTIONS FOR USE

Remove with hot water and in pressure possible greasy dirt residues, then apply the product as follows:

WITH PROPER FROTHERS:



use pure measuring water and air quantity: wait 10-15 minutes for the foam to collapse and wash away with water

WITH NEBULIZERS, PRESSURE WATER MACHINE, BY IMMERSION, FOR MANUAL OPERATIONS:

Dilute in water 1-5%, leave on 10 minutes and wash away with water.

PACKAGING:	Standard packages		N° pieces for carton	N° cartons / packages for pallet	N° pieces for pallet
	Tank	Kg 24		-	-
GIR/IBC	Kg 1100		-	-	1

CHEMICAL-PHYSICAL INFORMATIONS:	Parameters	U.M.	Values	Method of analysis
	Aspect:	-	Liquid	Visual
	Colour:	-	Colourless	Visual
	Perfume:	-	No perfume	-
	pH (Sol 1%):	-	1,4 ± 0,5	Instrumental
Density:	-	Kg/dm ³	1,23 ± 0,05	By weighing

HAZARD: Reg. (CE) 1272/2008			H290: May be corrosive to metals H314: Causes severe skin burns and eye damage H400: Very toxic to aquatic life H411: Toxic to aquatic life with long lasting effects
	 DANGER 		

We recommend for use, packaging etc. to follow instruction on label and/or on safety data sheet. This technical data sheet nullifies and replaces any precedent edition.

Bettari Detergenti s.r.l.

Via Galileo Galilei n.2 - 25020 - Poncarale (BS)
 Tel. 030-2540330 - Fax 030-2540332
 info@bettari.it - www.bettari.it
 Cap. Soc. € 210.000 int. vers. REA BS n° 284088
 Reg. Impr. BS n°029-29243 - C.F./P.IVA 01428790172